

# Numerical Assessment of Fan Blades Screen Effect on Fan/OGV Interaction Tonal Noise

Charles Foulquié<sup>a,c</sup>, Sofiane Khelladi<sup>a,\*</sup>, Michael Deligant<sup>a</sup>, Luis Ramírez<sup>b</sup>,  
Xesús Nogueira<sup>b</sup>, Jacky Mardjono<sup>c</sup>

<sup>a</sup> *Arts et Metiers Institute of Technology, CNAM, LIFSE, HESAM University, F-75013  
Paris, France*

<sup>b</sup> *Group of Numerical Methods in Engineering, GMNI, Universidade da Coruña, A Coruña,  
Spain*

<sup>c</sup> *Safran Aircraft Engines, Rond-point René Ravaud, 77550 Reau, France*

---

## Abstract

This work deals with sound generation and transmission in a fan stage. The study is done on a subsonic Fan stage and interaction noise between the fan wakes and the Outlet Guide Vanes (OGV) is considered. For this purpose, the Linearized Euler Equations (LEE) are solved with a steady axisymmetric flow. The acoustic sources are modelled by a scattering approach. Numerical simulations are carried out in an unwrapped cylindrical layer using a high-order finite volume solver. In order to explicitly take into account the moving fan blades into the propagation medium, a high-resolution sliding mesh technique is used. The simulation results, which highlight the screen effect of moving fan blades on fan/OGV interaction tones, are consistent with analytical literature.

*Keywords:* Aeroacoustics, turbojet fan noise, Outlet Guide Vane, turbomachines, Linearized Euler Equations, screen effect, fan, high order finite volumes

---

## 1. Introduction

The increase in the turbojet bypass ratio has resulted in the relative emergence of fan noise by comparison with other noise sources. On modern archi-

---

\*Corresponding author

Email address: [sofiane.khelladi@ensam.eu](mailto:sofiane.khelladi@ensam.eu) (Sofiane Khelladi)

March 30, 2020

tectures, Fan noise is practically predominant at all operating engine speeds.

- 5 Many aeroacoustic mechanisms are at the origin of Fan noise. Their occurrence and their intensity are strongly correlated with the system configuration and the operating conditions. In particular in subsonic Fan stages, the interaction noise generated by the fan wakes impingement on downstream Outlet Guide Vanes (OGV) is predominant. This source of noise has been widely studied  
10 using analytical, semi-analytical or more advanced numerical methods [1].

The screen effect of fan blades rotation on acoustic waves generated by the fan/OGV interaction remains difficult to take into account outside analytical studies [2, 3, 4, 5, 6]. These works, which are theoretically useful to understand acoustic transmission through the fan stage, suffer from consequent limitations  
15 on the geometry representation and the flow intricacy. In most current numerical models, the screen effect is either neglected [7] or implicitly taken into account [8, 9, 10].

In the case of hybrid approaches based on acoustic analogies, the calculations are performed in two steps. In the first step, an unsteady CFD analysis is  
20 conducted to obtain the acoustic sources. In the second step, the propagation of acoustic waves from these sources is either modeled by a Green's function [7] or calculated using a propagation operator [11]. As far as semi-analytical methods are concerned, the use of a suitable analogy [12] certainly allows us to take into account the effect of the rotating average flow (swirl). However, the  
25 formalism using analytical Green's functions, in their usual form, does not allow to include the fan blades screen effect.

The numerical resolution of a propagation operator allows to reproduce sound propagation from sources through the fan. However, the use of a propagation operator with source terms involves the risk of counting some propagation  
30 effects several times, due to the lack of an adapted theoretical basis which permits the clean separation of the mechanisms of generation and propagation in the presence of swirling flow. Moreover, and beyond this consideration, the question of the stability of the operator arises. Despite these drawbacks, approaches based on acoustic analogies have been used in [10] for instance. In

35 their work, the effect of the fan is not explicitly taken into account. Instead,  
the authors integrate in the source term all the mechanisms of generation and  
propagation inside the Fan-OGV stage.

An alternative to the approaches based on acoustic analogies is the direct  
resolution of Navier-Stokes equations. For obvious reasons of calculation cost,  
40 the “zonal” approach is considered in most cases. Simulations using Navier-  
Stokes equations are restricted to the Fan-OGV region, whereas the propagation  
inside the terminations (inlet/outlet), is taken into account by a non-viscous  
model. The connexions between the regions are done by using a mode-matching  
technique [8, 9, 13]. Using high-fidelity simulation of coupled Fan/OGV system  
45 [13], most of underlying physics is taken into account. In particular, it allows to  
capture both the screen effect of the fan on the acoustic waves and the feedback  
of acoustic waves on the fan wakes generation [1].

High-fidelity direct computation of radiated noise is still expensive and hy-  
pothesis on the flow can be done to make it more accessible [14]. Considering  
50 only the sound generation, Fan/OGV interaction tones are often modelled with  
inviscid flows [15, 16, 17, 18, 19]. The calculations can be carried out with linear  
equations when the hypothesis of small perturbations is verified [19, 20]. Of-  
ten, a non-linear computation is performed to take into account the nonlinear  
interactions due to the perturbations of large amplitudes [15, 16, 17, 18]. A  
55 linearized viscous equation system has also been employed with no significant  
improvement in accuracy [21].

In this work we present a numerical strategy based on the linearized Eu-  
ler equations (LEE) which explicitly takes into account the screen effect of the  
fan blades on the fan/OGV interaction tones. In the context of linearized ap-  
60 proaches, a steady state simulation is required to characterize the mean flow field  
[21]. Here, we propose to use a RANS calculation with a mixing plane interface  
to characterize a theoretical average flow field which is supposed axisymmet-  
ric. This simulation is also exploited to extract speed deficits downstream of  
the fan. The obtained velocity profile feeds a Gaussian wake model which only  
65 accounts for the coherent part of the wake. In this type of computation, the

vortical-mode scattering on the OGV vanes is usually calculated by convection of the perturbation. Here, in order to simplify the numerical implementation, the disturbance is imposed on the OGV by using a scattering approach based on the frozen gust assumption. No simplifying hypothesis were formulated on the  
70 geometry of the blades. The whole strategy of simulation is sketched in figure 1.




Figure 1: Sketch of the simulation strategy.

The calculations are carried out in an unwrapped cylindrical layer of a representative fan stage for two subsonic operating points<sup>1</sup>. The two dimensional approximation of the steady flow is done by assuming an equilibrium between the pressure and the centrifugal forces along the cylindrical layer. The numerical simulation is done in the time domain by using a high-order finite volume solver  
75

---

<sup>1</sup>The cylindrical layer is extracted at 80% of the fan leading edge radius. The study is done with 41% and 61% of the fan nominal rotation speed where 61%Nm nominal rotation speed corresponding to the “approach point”

based on Moving Least Squares (MLS) approximations. The relative motion between the fan blades and the OGV blades is handled through a high-resolution sliding mesh technique. A novel technique for considering periodic boundary  
80 conditions in turbofan simulations is also proposed.

The proposed approach aims to highlight some key mechanisms, often not discussed in the literature. It concerns the transmission of modes through a rotating blade cascade. An incident mode on a rotor experiences frequency and modal scattering where scattered modes can be regenerated at other harmonics  
85 of the blade-passing frequency (BPF) and orders shifted by a multiple of the blade number.

This paper is organized as follows. The modelling and the calculation procedure are presented in section II. The numerical method used to solve LEE in presence of rotating bodies and complex geometries is then briefly described in  
90 section III. The last section presents the numerical simulations and the assessment of screen effect.

## 2. Modelling and calculation procedure

### 2.1. Governing equations

In the propagation medium, the effect of viscosity is neglected and small  
95 perturbations are assumed ( $|\rho'| \ll \bar{\rho}$ ,  $|p'| \ll \bar{p}$ ), so the linearized Euler equations (LEE) are used. The steady part of the flow is written as  $\bar{\mathbf{U}} = [\bar{\rho}, \bar{\rho}\bar{\mathbf{v}}, \bar{p}]^T$  and the fluctuating part read as  $\mathbf{U}' = [\rho', \bar{\rho}\mathbf{v}', p']^T$ . The LEE equations written in conservative variables form read :

$$\begin{cases} \frac{\partial \rho'}{\partial t} + \nabla \cdot (\bar{\rho}\mathbf{v}' + \rho'\bar{\mathbf{v}}) = 0 \\ \frac{\partial(\bar{\rho}\mathbf{v}')}{\partial t} + \nabla \cdot (\bar{\rho}\bar{\mathbf{v}} \otimes \mathbf{v}' + p' \mathbf{I}) + (\nabla \otimes \bar{\mathbf{v}})^T \cdot (\rho'\bar{\mathbf{v}} + \bar{\rho}\mathbf{v}') = 0 \\ \frac{\partial(p')}{\partial t} + \nabla \cdot (p'\bar{\mathbf{v}} + \gamma\mathbf{v}') + (\gamma - 1)(p'\nabla \cdot \bar{\mathbf{v}} - \mathbf{v}' \cdot \nabla(\bar{p})) = 0 \end{cases} \quad (1)$$

### 2.1.1. Two-dimensional assumption

100 The LEE system 1 is considered along a cylindrical layer of the fan-OGV  
stage. This two-dimensional analysis assumes that there is an equilibrium be-  
tween the pressure and the centrifugal forces along the cylindrical layer. In  
other words, this approach is only valid for cases with no radial shifts of the  
meridional streamlines (for example configurations with constant hub and tip  
105 radius at the design point [22]). In a real fan stage, the angle of the spinner  
makes invalid this approach for low values of the radius. However, when the  
analysis is done for middle/high values of the radius of a conventional fan stage,  
the two-dimensional assumption remains acceptable.

110 The configuration investigated here is an industrial demonstrator of a con-  
ventional high bypass ratio fan OGV stage with a scale of 1 : 2. As shown in  
figure 2, the study is carried out on a cylindrical layer at 80% of the fan leading  
edge radius for two subsonic reduced speeds: 41% and 61% of the nominal ro-  
tation speed. Since the angle ( $\phi$ ) of the velocity of the steady flow is less than  
115 5° all along the axial direction in both operational points, the error introduced  
by the proposed approach is acceptable.




Figure 2: Fan-OGV geometry (courtesy of MAESTRO project of Safran Aircraft Engines). The cylindrical cut is made at 80% of the leading edge radius

### 2.1.2. Steady Flow Modelling

First, an axisymmetric modelling of the mean flow is done by averaging the flow in the azimuthal direction. Obviously, the two-dimensional assumption leads to neglect the radial component of the flow and the mean flow modelling reads :

$$\bar{\mathbf{v}} = \bar{v}_z(z) \mathbf{e}_z + \bar{v}_\theta(z) \mathbf{e}_\theta \quad (2)$$

A uniform mean flow is considered in the axial direction all along the fan-OGV stage :

$$\bar{v}_z(z) = V_z \quad (3)$$

The azimuthal component of the mean flow is assumed to be uniform inside of the fan region and equal to zero outside. A relatively weak gradient is applied to the interfaces between the regions using an hyperbolic tangent function. Finally the azimuthal component of the mean flow all along the fan-OGV stage is written as :

$$\bar{v}_\theta(z) = \frac{V_\theta}{2} \left( \tanh \left( \frac{z - z_a}{k_a} \right) - \tanh \left( \frac{z - z_b}{k_b} \right) \right) \quad (4)$$

where  $V_\theta$  is the uniform swirl component and  $z_a, z_b, k_a, k_b$  are the hyperbolic tangent function parameters. The uniform swirl component of the mean flow  $V_\theta$  is modelled as a linear combination of a rigid body rotation and a free vortex [22] as

$$V_\theta = \Omega_f r_c + \Gamma / r_c \quad (5)$$

where  $\Omega_f$  is the rotation speed of the fan,  $\Gamma$  the intensity of the free vortex and  $r_c$  is the radius of the cylindrical layer.

The parameters  $V_z, \Gamma, z_a, z_b, k_a, k_b$  are obtained from a RANS simulation performed beforehand.

## 2.2. Source modelling

<sup>135</sup> The acoustic sources are modelled in two steps. First, the fan wakes are approximated by using a Gaussian model. Then, in order to avoid computing the convection of the fan wakes, the scattering formulation of LEE equations is used to model the interaction noise generated by the fan wakes impingement on downstream OGV.

### 2.2.1. Wake Modelling

<sup>140</sup> We use a wake model initially proposed as part of an analytic methodology [23]. This model is based on the hypothesis that wakes are convected, incompressible and pressure-free. Furthermore, the incident speed deficit is modeled using a Gaussian distribution. The validity of this Gaussian modelling has been shown experimentally [24]. The wake of a fan blade  $k$  is defined as follows

$$\mathbf{u}'_{v,k} = u_0(z) \exp \left\{ -\xi \left( \frac{r_c \theta + \Delta\theta(z)}{b(z)} \right)^2 \right\} \mathbf{e}_\beta \quad (6)$$

with  $\xi = \ln 2$ .  $u_0(z)$  and  $b(z)$  are the maximum deficit in the center of the wake and the half-width, respectively. Both of them are functions of axial position.  $\Delta\theta(z) = z / \tan \beta$  is the azimuthal phase shift due to swirl.

<sup>150</sup> The vorticity field generated by the set of fan blades is expressed as an infinite sum of the elementary profile in which the azimuthal periodicity is introduced.  $\Theta = 2\pi/B$  :

$$\mathbf{u}'_v = \sum_{k=-\infty}^{+\infty} \mathbf{u}'_{v,k}(\theta + k\Theta, z) \quad (7)$$

The source model defined above must be fed by the functions describing the half-width of the wake  $b(z)$  and the maximum deficit in the center of the wake  $V_0(z)$ . In the set of calculations, we will consider a function  $b(z)$  as constant. <sup>155</sup> The maximum deficit is modelled by a second Gaussian function centred on the leading edge of the OGV.

$$u_0(z) = u_0 \exp \left\{ -\xi' \left( \frac{z - d}{b'} \right)^2 \right\} \quad (8)$$

with  $\xi' = \ln(2)$  and  $b' = 0.05$ . The distance between the leading edge of the stator blades and the half chord line of the rotor blades is given by  $d$ . The wake model and associated parameters are shown in figure 3.




Figure 3: Fan-wakes modelling (cylindrical cut in the reference frame  $(z, \theta)$ ).

<sup>160</sup> *2.2.2. Scattering formulation*

The scattering formulation of LEE allows solving a problem of sound generation by a gust-airfoil interaction without computing the convection of the gust. A major advantage of this formulation is that the treatment of boundary conditions is facilitated.

<sup>165</sup> The scattering formulation consists in rewriting the field of fluctuating velocities by separating the wakes velocity, denoted by  $\mathbf{u}'_v$ , from the velocity field scattered by the OGV, denoted by  $\mathbf{u}'_a$ , as

$$\mathbf{v}' = \mathbf{u}'_v + \mathbf{u}'_a \quad (9)$$

By assuming that the wakes disturbances are solenoidal and convected with the mean flow (frozen gust assumption), this approach allows solving the system

<sup>170</sup> of equations 1 by considering only the scattered field [25], as follows

$$\begin{cases} \frac{\partial \rho'}{\partial t} + \nabla \cdot (\bar{\rho} \mathbf{u}'_a + \rho' \bar{\mathbf{v}}) = 0 \\ \frac{\partial(\bar{\rho} \mathbf{u}'_a)}{\partial t} + \nabla \cdot (\bar{\rho} \bar{\mathbf{v}} \otimes \mathbf{u}'_a + p' \mathbf{I}) + (\nabla \otimes \bar{\mathbf{v}})^T \cdot (\rho' \bar{\mathbf{v}} + \bar{\rho} \mathbf{u}'_a) = 0 \\ \frac{\partial(p')}{\partial t} + \nabla \cdot (p' \bar{\mathbf{v}} + \gamma \mathbf{u}'_a) + (\gamma - 1)(p' \nabla \cdot \bar{\mathbf{v}} - \mathbf{u}'_a \cdot \nabla(\bar{p})) = 0 \end{cases} \quad (10)$$

Using this system of equations, the scattered acoustic wave now originates from the boundary condition on the OGV. Note that the frozen gust assumption is valid only if the turbulence velocities are weak and the convected distance is not much greater than a blade chord, which is the case in the present study<sup>2</sup>.

<sup>175</sup> By assuming that only velocity fluctuations normal to the OGV boundary are likely to interact with the OGV, the noise scattered on OGV from fan wakes disturbances can be computed. For this purpose we must consider that the total velocity on a point located on the OGV is given by  $\mathbf{v} = \bar{\mathbf{v}} + \mathbf{u}'_v + \mathbf{u}'_a$ . Since the normal component of the total velocity is zero ( $\mathbf{v} \cdot \mathbf{n} = 0$ ) at the OGV boundaries and assuming that  $\bar{\mathbf{v}} \cdot \mathbf{n} = 0$  we obtain:

$$\mathbf{u}'_a \cdot \mathbf{n} = -\mathbf{u}'_v \cdot \mathbf{n} \quad (11)$$

where  $\mathbf{n}$  is a unit vector along the local normal of OGV boundaries and the wake velocity ( $\mathbf{u}'_v$ ) is given by the model introduced in the previous paragraph.

<sup>185</sup> Finally, the problem is to solve the system of equations 10 with the boundary condition on the surface of OGV prescribed by equation 11. It is important to note that this approach is exact only when a gust-plate interaction is considered. The computation of noise radiated from a flat plate subjected to a normal incidence gust is proposed in the Appendix 5 as a validation test case for this approach.

---

<sup>2</sup>In the present case, the turbulence is only a few per cent of the mean flow speed. Also, fan wakes are extracted from a RANS simulation at the mixing plane location which is located about one fan blade chord away from the OGV leading edge.

<sup>190</sup> **3. Numerical method**

*3.1. General framework*

*3.1.1. Finite volume discretization in ALE formulation*

The finite volume formulation for LEEs in conservative form reads :

$$\int_A \frac{\partial \mathbf{U}}{\partial t} + \mathbf{H}(\mathbf{U}) dA = - \oint_{\Gamma} \mathcal{F}(\mathbf{U}) \cdot \mathbf{n} d\Gamma \quad (12)$$

where  $\mathcal{F}(\mathbf{U})$  is the flux matrix and the vector  $\mathbf{H}(\mathbf{U})$  contains the refraction terms.  $\mathcal{F}(\mathbf{U}) \cdot \mathbf{n}$  is the normal flux crossing the inter-cell boundary,  $A$ ,  $\Gamma$  and <sup>195</sup>  $\mathbf{n}$  are respectively the area, the contour and the normal to the control surface. In order to account for the relative motion of the rotor with respect to the stator, the sliding mesh technique is used. This technique requires the use of an Arbitrary Lagrangian-Eulerian (ALE) formulation. The equations are written in a reference frame which moves with the grid. The flux matrix  $\mathcal{F}(\mathbf{U})$  and the vector  $\mathbf{H}(\mathbf{U})$  in ALE formulation read <sup>200</sup>

$$\mathcal{F}(\mathbf{U}) = \begin{pmatrix} \bar{\rho}\mathbf{v}' + \rho'(\bar{\mathbf{v}} - \bar{\mathbf{v}}_g) \\ \bar{\rho}(\bar{\mathbf{v}} - \bar{\mathbf{v}}_g) \otimes \mathbf{v}' + p'\mathbf{I} \\ p'(\bar{\mathbf{v}} - \bar{\mathbf{v}}_g) + \gamma\bar{p}\mathbf{v}' \end{pmatrix}, \quad \mathbf{H}(\mathbf{U}) = \begin{pmatrix} 0 \\ (\nabla \otimes \bar{\mathbf{v}})^T \cdot (\rho'\bar{\mathbf{v}} + \bar{\rho}\mathbf{v}') \\ (\gamma - 1)(p'\nabla \cdot \bar{\mathbf{v}} - \mathbf{v}' \cdot \nabla(\bar{p})) \end{pmatrix}$$

where  $\bar{\mathbf{v}}$  and  $\bar{\mathbf{v}}_g$  are, respectively, the mean flow velocity and the grid velocity at cell interface boundary. Note that the grid velocity  $\bar{\mathbf{v}}_g$  is subtracted from the mean flow velocity  $\bar{\mathbf{v}}$  in the flux matrix, whereas the refraction vector  $\mathbf{H}(\mathbf{U})$  remains unchanged. <sup>205</sup>

*3.1.2. Generalized Godunov-type scheme*

The implementation of the finite volume method is done using a generalized Godunov-type scheme. This kind of scheme can be broken down into two stages : the “projection” stage, which is exclusively of numerical nature and the <sup>210</sup> “evolution” stage which holds the physics.

In the original Godunov’s scheme [26] the projection stage is ensured by a piecewise constant approximation of the variables. Of course by doing a piecewise constant approximation (cell averages), part of the knowledge of the

original initial data is lost. Thus, the original Godunov's method, which is only  
<sup>215</sup> first order accurate in space and time, introduces excessive numerical dissipation. To address this problem, a high-order extension of Godunov-type finite volume method is needed. The key ingredient in this type of scheme is the piecewise polynomial approximation. Here, Moving Least Squares (MLS) [27] approximations are used for the computation of a high order accurate piecewise  
<sup>220</sup> polynomial approximation. For the sake of brevity, this approximation is shown in Appendix 5.

The evolution step consists in resolving the Riemann problem at each integration points of inter-cell boundaries (Flux computation). The solution can be computed exactly as long as the governing equations are linear. Thus, the flux  
<sup>225</sup> reads as follows

$$\mathcal{F}(\mathbf{U}_-, \mathbf{U}_+) \cdot \mathbf{n} = \frac{1}{2} (\mathcal{F}(U_-) + \mathcal{F}(U_+)) \cdot \mathbf{n} - \frac{1}{2} \sum_{k=1}^4 \alpha_k |\lambda_k| \mathbf{e}_k \quad (13)$$

where  $-$  and  $+$  refers respectively to the “left” and “right” Riemann states of the inter-cell boundaries.  $\mathbf{e}_k$  and  $\lambda_k$  are the eigenvector and the eigenvalues of the flux Jacobian [28] respectively.  $\alpha_k$  represent the wave strengths along the eigenvector direction. In the special case of grid motion, the set of eigenvalues becomes

$$\lambda_1 = (\bar{\mathbf{v}} - \bar{\mathbf{v}}_g) \cdot \mathbf{n} + \bar{c}, \quad \lambda_2 = (\bar{\mathbf{v}} - \bar{\mathbf{v}}_g) \cdot \mathbf{n} - \bar{c}, \quad \lambda_3 = \lambda_4 = (\bar{\mathbf{v}} - \bar{\mathbf{v}}_g) \cdot \mathbf{n} \quad (14)$$

The wave strengths and the eigenvectors remain unchanged with respect to a static mesh formulation.

### 3.1.3. Semi-discretized form and mass matrix inversion

The complete process of spatial discretization (flux quadrature, volumic term  
<sup>230</sup> discretization) is not described here for the sake of brevity. Readers can refer to [29] for more details. Let's assume that the spatial discretization leads to the following system :

$$\mathbf{M} \cdot \left( \frac{\partial \mathbf{U}}{\partial t} - \mathbf{H}(\mathbf{U}) \right) = \mathcal{R}(\mathbf{U}) \quad (15)$$

where  $\mathbf{U} = [\mathbf{U}_1, \dots, \mathbf{U}_N]^T$ ,  $\mathbf{H} = [H(\mathbf{U}_1), \dots, H(\mathbf{U}_N)]^T$ ,  $\mathcal{R}(\mathbf{U}) = [\mathcal{R}(\mathbf{U}_1), \dots, \mathcal{R}(\mathbf{U}_N)]^T$  is the residual matrix and  $\mathbf{M}$  is the mass matrix. System 15 is the semi-discretized form of system 3.1.1.

Using an explicit time integration scheme, it is required to compute the inverse of the mass matrix to solve the system

$$\frac{\partial \mathbf{U}}{\partial t} = \mathbf{M}^{-1} \mathcal{R}(\mathbf{U}) + \mathbf{H}(\mathbf{U}) \quad (16)$$

In general, a diagonal structure is recovered by enforcing reconstructions that preserve the mean. But this technique induces a loss of accuracy of the reconstructed variables, and it is not suitable for very high-order reconstructions [30]. This is why we prefer to be as accurate as possible even though this procedure leads to solve a system with non-diagonal mass matrix, which is more expensive in terms of computation time.

The inverse matrix can be computed by using a low-complexity approximation which consist in : (i) rewriting matrix  $\mathbf{M}$  as the subtraction of the matrix of perturbation  $\mathbf{E}$  from the identity matrix  $\mathbf{I}$  and by (ii) using the Neumann series [31] :

$$\mathbf{M}^{-1} = (\mathbf{I} - \mathbf{E})^{-1} = \sum_{k=0}^{p_{\text{Inv}}} \mathbf{E}^k + o(p_{\text{Inv}}) \quad (17)$$

The convergence criteria of this series expansion is verified as long as the spectral radius of the matrix  $\mathbf{E}$  is less than unity ( $\rho(\mathbf{E}) = \lambda_{\max}(\mathbf{E}) < 1$ ).

#### 3.1.4. Time integration

Time integration is performed by using a low storage five-stages fourth-order explicit Runge-Kutta scheme [32]. This scheme has a wider stability region than a standard explicit fourth-order Runge-Kutta scheme which allows using larger time steps.

255    3.2. Boundary conditions

3.2.1. Sliding mesh technique

In order to account for the relative motion between rotor and stator, here we use the sliding mesh technique proposed in [33]. In this technique, a halo-cell (or ghost-cell) is created as a mirror image of a given cell  $I$ . This is schematically presented in figure 4. In order to solve the Riemann problem between the halo-cell and the cell  $I$ , it is required to compute the value of the variables at the centroid of the halo-cell, so that the mean is preserved. In order to do that, a MLS approximation is performed at the position of the halo cell. MLS-shape functions are computed by using the stencil of the closest cell. This technique induces an error of mass conservation, but numerical experiments have shown that this error is of the same order of magnitude as the error in the variables when a fixed grid approach is used and the order of accuracy of the numerical scheme is preserved [33]. This approach avoids the computation of intersections used by most of the sliding mesh approaches, which introduces additional complexity in the coding and a high computational cost.




Figure 4: Halo-cell method for flux computation

We refer the interested reader to [33] for a complete description of the sliding mesh technique used in this work.

### 3.2.2. Natural periodic boundary conditions

Periodic boundary conditions are very useful in many situations where the  
 275 geometry of the simulated problem has a certain periodicity. When dealing with  
 large stencils (which is the case of high-order MLS stencils), the implementation  
 of a periodic boundary condition is not straightforward [34]. When sliding meshes  
 and periodic boundaries are considered together, the implementation becomes  
 more complex. Here, we propose a simple workaround which consist in wrapping  
 280 up the plane domain to a cylinder. Thus, the periodic boundary condition  
 is naturally ensured. Actually, there is no more periodic interface: the cells  
 connections are natural. This means that there is no special requirement on the  
 mesh for creating the linear interface. Wrapping rectangular plane domain into  
 a cylinder allows us to take into account periodic domain with a linear sliding  
 285 interface. The 3D cylinder and 2D unwrapped plane geometry are parametrized  
 as

$$\underbrace{\begin{cases} x = r_c \cos \theta \\ y = r_c \sin \theta \\ z \end{cases}}_{\text{3D cylinder geometry}} \Rightarrow \underbrace{\begin{cases} X = r_c \theta & [2\pi] \\ Y = z \end{cases}}_{\text{2D unwrap plane geometry}} \quad (18)$$

This 3D cylinder surface geometry is easily created, meshed and exported.  
 All cells are discretized facets of the cylinder. All exported points are on the  
 290 surface of the cylinder with coordinates verifying the left part of (18). In order  
 to avoid adding discretization errors due to the curvature of the surface, the  
 area of each cell is considered as the area of the cell on the cylinder surface (see  
 Figure 5). This area is computed using the  $\{X, Y\}$  variables. The positions  
 of the cell centroid, face centroid and integration points are also computed to  
 be on the cylinder surface. In order to compute the MLS shape functions it is  
 required to determine the distance  $d_{A \rightarrow B}$ , between two points  $A = X_A, Y_A$  and  
 295

$B = X_B, Y_B$ . In the curved surface, this distance can be computed as

$$\Delta X_{A \rightarrow B} = r_c \text{sign}(\theta_B - \theta_A) \min \{|\theta_B - \theta_A|, |\theta_B - \theta_A - 2\pi|\} \quad (19)$$

$$\Delta Y_{A \rightarrow B} = z_B - z_A \quad (20)$$

$$d_{A \rightarrow B} = \sqrt{(\Delta X_{A \rightarrow B})^2 + (\Delta Y_{A \rightarrow B})^2} \quad (21)$$




Figure 5: Close up to facet and real face on cylinder quadrature points (■), element centroid (●) and element nodes (○)

### 3.3. Numerical validation of the method

The purpose of this section is to test the accuracy of the numerical method.  
 300 In particular, the order of accuracy of the method is monitored on a cylindrical computational domain with a sliding interface.

#### 3.3.1. Test case description

The problem concerns the propagation of a Gaussian pulse in a medium at rest (without flow) through the reference domain  $\mathcal{D} = x \in [-l/2, l/2] \times y \in [-L/2, L/2]$ . In what follows, all variables are made non-dimensional by  $\bar{c}$  (ambient sound speed) for the velocity scale,  $\bar{\rho}$  (ambient density) for the density scale,  $\bar{\rho}\bar{c}^2$  for the pressure scale,  $\Delta$  for the length scale and  $\Delta/\bar{c}$  for the time scale. The Gaussian pulse is introduced in non-dimensional LEE ( $\bar{\rho} = 1$ ,  $\bar{c} = 1$ ,  $\bar{p} = 1/\gamma$ ) by initializing the vector of conservative variables as following :

$$\mathbf{U}_{x,y,t=0} = \epsilon e^{-\frac{\ln 2}{b} (\delta x^2 + \delta y^2)} [1, 0, 0, 1]^T \quad (22)$$

310 where  $\delta x = x - x_0$ ,  $\delta y = y - y_0$  and  $(x_0, y_0)$  is the Gaussian impulsion location.  $b$  and  $\epsilon$  are respectively the half-width and the amplitude of the Gaussian pattern.

As shown in figure 6, the reference domain has periodic boundaries conditions at the borders  $x = \pm l/2$  and non-reflecting ones at the borders  $y = \pm L/2$ . The impulsion is set at its center ( $x_0 = 0, y_0 = 0$ ). This means that when the 315 acoustic wave front reach the periodic boundaries a symmetric wave front enter the domain. The analytical solution of this test case is given by :

$$p'_{\text{exact}}(x, y, t) = \sum_{i=-\infty}^{+\infty} p'_{\text{gi}}(\delta x + l \times i, \delta y, t) \quad (23)$$

with  $p'_{\text{ig}}$  the analytical of a Gaussian impulsion alone :

$$p'_{\text{gi}}(x, y, t) = \frac{\epsilon}{2\alpha} \int_0^{\infty} \exp(-\frac{\zeta^2}{4\alpha}) \cos(t\zeta) J_0(\zeta r) \zeta d\zeta \quad (24)$$

where  $J_0$  is the Bessel function of the first kind and order zero,  $r = \sqrt{\delta x^2 + \delta y^2}$ .

Please consult [35] for details and mathematical proof.




Figure 6: Test case illustration

320 The computational domain is obtained by wrapping the plane domain of reference  $\mathcal{D}_r = x \in [-l/2, l/2] \times y \in [-L/2, L/2]$  into the  $y$ -direction. The resulting domain  $\mathcal{D}_c = \theta \in [-\pi, \pi] \times y \in [-L/2, L/2]$  is a cylinder with a radius

of  $r_c = l/2\pi$ . Note that the cylindrical domain has a circular sliding interface located at  $y = 0$ . This way, the computational grid is decomposed into two parts : a fixed grid for the inferior part ( $y < 0$ ) and a sliding grid for the superior part ( $y > 0$ ) which rotates around its center with a non-dimensional rotational velocity  $\omega$ . Since the rotation is not physical, the acoustic wave must propagate through the sliding grid without any alteration. The computational configuration is shown in figure 7

A cubic polynomial reconstruction ( $p = 3$ ) is used with the purpose of reaching the  $4^{th}$  order of accuracy. The convergence study is performed on unstructured grids and the comparison with analytical solution is done at time  $t_c = 30$ . The angular velocity of the sliding grid is set at  $\omega = 0.05$ . The time-step is set at  $\Delta t = 4.0 \cdot 10^{-1}$  for each computation.




Figure 7: 2D cylindrical computation with non-conform sliding interface ( $\omega = 0.05$ ) : a) wrapped domain ( $t=15$ ), b) unwrapped domain ( $t=0, 10, 20, 30$ ),  $\text{---} \cdot \text{---}$  sliding interface location.

### 3.3.2. Test case results

In order to quantify the numerical method accuracy, we define the local error at the center of an element of the mesh  $(\theta_i, y_i)$  at time  $t_c$  as

$$\delta p'_i = p'_{\text{num}}(r_c \theta_i, y_i, t_c) - p'_{\text{exact}}(x_i, y_i, t_c) \quad (25)$$

The error norms  $L_1$ ,  $L_2$  and  $L_\infty$  are defined as

$$L_1 = \frac{1}{A_D} \sum_{i=1}^N A_i |\delta p'_i| \quad L_2 = \frac{1}{A_D} \sqrt{\sum_{i=1}^N (A_i \delta p'_i)^2} \quad L_\infty = \max(|\delta p'_i|) \quad (26)$$

where  $A_D$  and  $A_i$  are respectively the surface of the whole domain and the surface of the element  $i$ . The point-by-point order of convergence  $\alpha_*^{(k+1)}$  based on the  $L_*$ -norm which is computed from mesh resolution (k) and (k-1) is defined as :

$$L_*^{(k)} = \left( \frac{h^{(k)}}{h^{(k-1)}} \right)^{-\alpha_*^{(k)}} L_*^{(k-1)} \quad (27)$$

where  $h^{(k)}$  is the characteristic element size of mesh resolution (k) and is given by  $h^{(k)} = \sqrt{A_D/N^{(k)}}$ . The convergence curves and values of the three error norms are given in figure 8 and table 1. This study show both the validity of the approach and the high order of accuracy of the method. Readers can refer to [33, 29] for more detail studies of the FV-MLS method in presence of sliding interface.




Figure 8: Accuracy curves for unstructured cylindrical grids with sliding interface. Test case parameters :  $\omega = 0.05$ ,  $t_c = 30$ ,  $b = 3$ ,  $\epsilon = 1$ ,  $l = 25$ ,  $L = 50$ ; FV-MLS parameters :  $p = 3$ ,  $n_{add} = 4$ ,  $\kappa = 5$ ,  $p_i = 1$ ,  $\Delta t = 4.0 \cdot 10^{-1}$ .

k	N	$h^{(k)}$	$L_2^{(k)}$	$\alpha_2^{(k)}$	$L_1^{(k)}$	$\alpha_1^{(k)}$	$L_\infty^{(k)}$	$\alpha_\infty^{(k)}$
1	676	2.72	$1.87 \times 10^{-2}$	0	$1.23 \times 10^{-2}$	0	$7.26 \times 10^{-2}$	0
2	900	2.36	$1.49 \times 10^{-2}$	1.59	$9.84 \times 10^{-3}$	1.57	$6.16 \times 10^{-2}$	1.15
3	2288	1.48	$5.14 \times 10^{-3}$	2.28	$3.10 \times 10^{-3}$	2.47	$2.80 \times 10^{-2}$	1.69
4	4206	1.09	$2.06 \times 10^{-3}$	3.00	$1.17 \times 10^{-3}$	3.21	$1.07 \times 10^{-2}$	3.16
5	8218	0.78	$5.49 \times 10^{-4}$	<b>3.95</b>	$3.04 \times 10^{-4}$	<b>4.02</b>	$3.03 \times 10^{-3}$	<b>3.76</b>

Table 1: Accuracy values for unstructured cylindrical grids with sliding interface. Test case parameters :  $\omega = 0.05$ ,  $t_c = 30$ ,  $b = 3$ ,  $\epsilon = 1$ ,  $l = 25$ ,  $L = 50$ ; FV-MLS parameters :  $p = 3$ ,  $n_{add} = 4$ ,  $\kappa = 5$ ,  $p_i = 1$ ,  $\Delta t = 4.0 \cdot 10^{-1}$ .

## 4. Numerical simulations and analysis of results

### 4.1. Numerical setting

The calculations are done at 80% of the fan leading edge radius of a representative fan stage designed by Safran Aircraft Engines. This fan stage has non-trivial common divisors between the number of fan blades ( $B = 24$ ) and the number of OGV blades ( $V = 30$ ). The greatest common divisor is  $\text{gcd}(B, V) = 6$ . As a result, by introducing a periodicity condition in the computational domain, a simulation can be conducted on a reduced sector of angle  $\theta = \pi/3$ . As shown schematically in figure 9, the resulting cylinder sector of angle  $\alpha = \pi/3$  and radius  $r_c$  is wrapped into a full cylinder of radius  $r'_c = 2\pi/\alpha \times r_c$ . This way a natural periodic condition appears. Note that the angular rotational velocity of the Fan  $\Omega_f$  shall be replaced by  $\Omega'_f = r_c/r'_c \times \Omega_f$ .




Figure 9: Natural periodicity condition by wrapping the calculation domain ; Reduced computational domain a) Before transformation (cylinder sector of angle  $\alpha = \pi/3$ , radius  $r_c$ , height  $h$  and angular rotational velocity of the sliding part  $\Omega_f$ ), b) After transformation (full cylinder of radius  $r'_c = 2\pi/\alpha \times r_c$ , height  $h$  and reduced angular velocity of rotation of the sliding part  $\Omega'_f = r_c/r'_c \times \Omega_f$ )

The sliding interface is located halfway between the fan and the OGV. The transfer of information through the interface is ensured by the method of the ghost cell [33]. Sponge zones upstream and downstream are used to dissipate some of the energy and thus avoid spurious reflections of the waves leaving the

domain. In order not to compute the fan wakes convection into the simulation, the computation is carried out with the scattering formulation. Thus, the wakes speed deficits are applied directly to the skin of the OGV. Finally, reflective boundary conditions are used to model the action of fan blades on the acoustic mode. A sketch of the computational domain and the setup of the problem is shown in figure 10.




Figure 10: Schematic view of the flow and boundary conditions.

The computational domain is divided into triangular element and a cell-centered configuration is adopted. The cylindrical computational mesh used for the computation is shown in fig. 11. The FV-MLS method is used with a cubic polynomial reconstruction ( $p = 3$ ) in order to reach the 4<sup>th</sup> order of accuracy. The number of elements of the computational mesh and the time step used depend on the engine speed. Thus, for the 41%Nm regime we choose  $N \sim 13 \cdot 10^3$  elements and  $dt = 3.5 \cdot 10^{-3}ms$ , whereas we choose  $N \sim 23 \cdot 10^3$  elements and  $dt = 1.8 \cdot 10^{-3}ms$  for the 61%Nm regime.




Figure 11: View of the computational mesh used for the  $61\%Nm$  regime ( $N = 23 \cdot 10^3$ ).

In order to study separately the effect of the swirl effect and the screen effect, the calculations were carried out on three configurations (see figure 12). In the first configuration we consider the OGV alone with axial flow (“OGV-axial”).  
375 In the second configuration, the OGV is considered alone with swirling flow (“OGV-swirl”). Finally, we consider the Fan-OGV with swirling flow (“FAN-OGV-swirl”).




Figure 12: The three different configurations selected for the study : a) OGV-axial , b) OGV-swirl , c) FAN-OGV-swirl .

#### 4.2. Time-domain results

In this part, the results are presented in the time domain. First, figure 380 13 presents a  $360^\circ$  visualization of the pressure field in the FAN-OGV-swirl configuration for the two regimes  $41\%Nm$  and  $61\%Nm$ . This representation of the results is obtained by partially unwinding the computational grid so that it matches the curvature of the cylindrical layer of radius  $r_c$ . Then, the domain 385  $360^\circ$  is reconstructed by reproducing the periodic pattern as many times as necessary (6) with the appropriate azimuth offset ( $\pi/3$ ). Using this visualization, the acoustic screen effect appears important whatever the rotation regime.




Figure 13: Domain reconstruction  $360^\circ$  (FAN-OGV-swirl configuration); visualization of the pressure at time  $t = 10$  ms for the two engine speeds: a)  $41\%Nm$  , b)  $61\%Nm$  . Cut radius  $r_c = 0.8 \cdot R$ .

In order to analyze the pressure field, it is preferable to visualize the unrolled surface. In the figure 14, the results are exposed for the  $41\%Nm$  regime by displaying the half (angle sector  $180^\circ$ ) of the cylindrical surface.




Figure 14: Results of acoustic pressure for  $180^\circ$  in the unwrapped cut for the  $41\%Nm$  regime. From left to right: OGV-axial , OGV-swirl and FAN-OGV-swirl configurations. Cut radius at  $r_c = 0.8 \cdot R$ .

390 The OGV-axial configuration shows that some coherent wave fronts stand out. These wave fronts or azimuthal modes ( $m$ ) can be numbered according to their orientation<sup>3</sup> and number of pressure variation cycles (on  $360^\circ$  in the azimuthal direction) that compose them. By adopting this convention, one easily finds on the OGV-axial configuration at  $41\%Nm$  regime the modes  $m = -6$   
 395 and  $m = +18$  propagating upstream of the OGV grid. At first sight, the presence of the tangential flow seems to cut out the mode  $m = +18$  on the one hand (see figure 14-OGV-swirl -41%Nm ) and the addition of the fan (see figure 14-FAN-OGV-swirl -41%Nm ) appears to disturb the wave fronts considerably.

---

<sup>3</sup>positive (+) if  $\mathbf{n} \cdot \mathbf{u}_\theta > 0$  or negative (-) if  $\mathbf{n} \cdot \mathbf{u}_\theta < 0$ , with  $\mathbf{n}$  the normal at the wavefront and  $\mathbf{u}_\theta$  the azimuth direction of reference

400 Moreover, the checkerboard patterns shown in figure 14 illustrates clearly the interference between oblique waves of opposite rotation when unwrapped as two-dimensional maps. For instance, the Fan-OGV-swirl configuration seems to regenerate the mode  $m = +18$  compared to the OGV-swirl configuration.

405 It can be seen from the figure 15, with the same color scale than figure 14, that the radiation structure for the  $61\%Nm$  regime is equivalent to that of the  $41\%Nm$  regime. The wave fronts are simply narrower and their inclination larger. The swirl and screen effects detected for the  $41\%Nm$  regime also appear in this configuration. Notice that the cut-off of the mode  $m= +18$  does  
410 not occur anymore.




Figure 15: Results of acoustic pressure for  $180^\circ$  in the unwrapped cut for the  $61\%Nm$  regime. From left to right: OGV-axial , OGV-swirl and FAN-OGV-swirl configurations. Cut radius at  $r_c = 0.8 \cdot R$ .

In order to quantify the screen effect, the acoustic levels for the OGV-swirl and FAN-OGV-swirl configurations were calculated for three distinct azimuthal positions: a) upstream of the fan, b) between the fan and the OGV, c) downstream of the OGV.

415 Figure 15 also points out that at higher rotational velocity and corresponding

axial-flow speed, the same modes are farther beyond the cut-off limit because their driving frequency increases, this is associated to shorter wavelength and smaller wavefront angles with respect to the vane-cascade front.

420 The results are compiled in Figure 16. The average azimuthal acoustic level upstream of the fan is reduced by 1.6dB for the  $41\%Nm$  regime and by 4.3dB for the  $61\%Nm$  regime. Notice that sound is clearly increased downstream at  $61\%Nm$  regime.

425 The observation is limited because the superposition of acoustic modes makes it difficult to identify and quantify the physical mechanisms. A modal analysis is necessary in order to better analyse the evolution of the modal signature from one configuration to another.




Figure 16: Comparison of acoustic sound pressure levels on three successive cross sections((a)  $z=20$  mm, (b)  $z=-10$  mm, (c)  $z=-40$  mm) and for each regime ;  $41\%Nm$  (left) and  $61\%Nm$  (right). — FAN-OGV-swirl — OGV-swirl

#### 4.3. Frequency-domain results

As it has been observed on the pressure field  $p(x, \theta, t)$ , the response is not 430 only periodic in time, but also periodic in the azimuthal direction. For a given axial position, the acoustic pressure, computed at  $N_t$  instants samples a time

interval  $T = k/BPF$  and  $N_\theta$  angular positions, sampling a spatial interval  $\Theta = 2\pi$ . Thus, the acoustic pressure can be decomposed using a Fourier series in space and time. This transform provides a representation of the solution as a function of the harmonic ( $n$ ) and the azimuth modes ( $m$ ) for each axial position (x) :

$$P_{mn}(x) = \frac{2}{N_\theta N_t} \sum_{l=0}^{N_\theta-1} \sum_{j=0}^{N_t-1} p_{lj}(x) \exp\left(-i\frac{2\pi nj}{N_t}\right) \exp\left(-i\frac{2\pi ml}{N_\theta}\right) \quad (28)$$

where  $p_{lj}(x)$  and  $P_{mn}(x)$  are the contractions of  $p(x, \theta_l, t_j)$  and  $P(x, m, n)$ . Moreover,  $n = 0, \dots, N_t/2$  and  $-N_\theta/2 < m < N_\theta/2$ . Finally, the Fourier series in space and time allows to know the amplitude of each elementary wave, defined by its harmonic  $n$  and its azimuth mode  $m$ , according to the axial position  $x$ . The results of the modal analysis as a function of the axial position  $z$  for each regime and each configuration are presented in figure 17.

The tonal interaction noise resulting from the interaction mechanism between a rotor and a stator (both homogeneous) is modelled analytically by Tyler-Sofrin's rule [36]. This rule, verified experimentally, predicts the modal structure of the radiated noise. According to it, the excited azimuthal modes are :

$$m = nB - lV \quad (29)$$

where  $B$  and  $V$  are respectively the number of fan blades and the number of OGV blades,  $n$  is the harmonic of the blade passing frequency (BPF) tone and  $l \in \mathbb{Z}$  is an arbitrary integer. This result can be interpreted as a phenomenon of interference between the phase-shifted pressure fields coming from each OGV blade.

As shown in figure 17, the computed modal signature respects the Tyler-Sofrin's rule (hot colors correspond to dominant modes). Considering the OGV-axial configuration, we find in particular the dominant mode  $m = -6$  which propagates at the blade passing frequency ( $n = 1$ ) that have been previously




Figure 17: Modal analysis along the  $z$ -axis for the blade passing frequency ( $n = 1$ ) and the first two harmonics( $n = 2, 3$ ): a) 41% Nm regime, b) 61% Nm regime.

identified on the time-domain results. The screen effect on this mode is even more important than the effect of swirl. Indeed, we note for both rotation regimes a very clear decrease in amplitude around the fan (configuration FAN-  
460 OGV-swirl ). Whatever the configuration considered, the interaction mode  $m = +24$ , which is generated at the blades passing frequency ( $n = 1$ ) is cut-off. Cut-on modes of higher harmonics ( $m = -12, m = +18, m = -18, m = +12$ ) are all affected by swirl on the one hand and by the screen effect on the other hand:

- 465
- The mode  $m = -12$  ( $n = 2$ ) behaves independently of the regime and very similarly to the mode  $m = -6$  ( $n = 1$ ).
  - The mode  $m = +18$  ( $n = 2$ ) is cut-off by the swirl for the 41%Nm regime while remaining cut-on in presence of swirl for the 61%Nm regime. This mode is then, independently of the regime, fed by the fan.

- 470 - The mode  $m = -18$  ( $n = 3$ ) is not affected by the swirl and a reflection mechanism on the fan is visible for the  $41\%Nm$  regime. Considering the  $61\%Nm$  regime, the mode  $m = -18$  is fed by the swirl.
- The mode  $m = +12$  ( $n = 3$ ) has a very low intensity for the first two configurations. The amplitude of the mode increases as the fan passes for  $41\%Nm$  regime while remaining stable for the  $61\%Nm$  regime.
- 475

#### 4.3.1. Cut-off condition and swirl

The azimuthal interaction modes are generated at the harmonic of the blade passing angular frequency  $nB\Omega_f$  with a speed of rotation  $nB\Omega_f/m$ . The cut-off condition can be expressed as a function of the relative Mach number of the spinning mode  $M_m^r$  [37, 38] which is defined as :

$$M_m^r = \sqrt{M_z^2 + (M_\theta + M_m)^2} < 1 \quad (30)$$

where  $M_z = V_z/\bar{c}$  is the axial Mach number,  $M_\theta = V_\theta/\bar{c}$  is the maximum azimuthal Mach number and  $M_m = nB\Omega_f r_c/m\bar{c}$  is the absolute Mach number of the spinning mode. The mode is cut-off if the relative Mach number of mode  $M_m^r$  is subsonic <sup>4</sup> ( $M_m^r < 1$ ) [37, 38].

485 The figure 18-a) shows the classical mode-frequency diagram for the OGV-axial -  $41\%Nm$  configuration. The branches of the "V-shape" (which are based on the cut-off relation 30) point the limits of the cut-off zone (outside the "V"). For example, the interaction mode  $m = +24$  ( $n = 1$ ) which is outside the "V" is cut-off. Note that in pure axial flow ( $M_\theta = 0$ ) the branches of the "V-shape" 490 are symmetric.

In accordance with the cut-off relation 30, a mode close to a branch turns from cut-on to cut-off or vice versa because of the swirl, depending on its either co-rotating or contra-rotating spinning phase. This is the case of the mode  $m = +18$ . As shown in figure 18-b), in the presence of swirl the "V-shape"

---

<sup>4</sup>Note that the converse of this assertion is not true: A supersonic relative Mach number is a necessary but not a sufficient condition allowing a mode to be cut-on.

<sup>495</sup> rotates counter-clockwise around its apex and the mode  $m = +18$  turns from cut-on to cut-off. This way, the present numerical results in both OGV-axial and OGV-swirl are consistent with the cut-off relation 30. Note that the relative Mach number of spinning modes increase for the  $61\%Nm$  regime and the mode  $m = +18$  remains cut-on in the presence of swirl.




Figure 18: Distribution of acoustic energy on mode-harmonic diagram ( $m, n$ ) at the axial location  $z = 0\text{mm}$  and  $41\%Nm$  regime for configuration : a)OGV-axial , b)OGV-swirl . The expected position of Taylor and Sofrin's modes are spotted by a circle on the diagram. The “V-shape” cut-off limit is represented by red lines. Colour scale is arbitrary in this illustration.

#### <sup>500</sup> 4.3.2. Fan blades screen effect

The computed modal signature highlight two distinct mechanisms : a frequency and modal scattering and a reflection mechanism. The frequency and modal scattering of the rotor is known to obey to a simple relationship. The incident azimuthal modes  $nB - lV$  which are generated at the harmonic of the blade passing angular frequency  $nB\Omega_f$  are regenerated in scattered azimuthal modes  $(n+1)B - lV$  at associated angular frequencies  $(n+1)B\Omega_f$ . A detailed analysis has been published in a report by Hanson [39].

<sup>510</sup> As shown in figure 19, the scattering rule makes the mode  $m = +18$  indeed expected at  $2\text{BPF}(n = 2)$  from the mode  $m = -6$  at  $\text{BPF}(n = 1)$  in both configurations. It should be noted that at  $41\%Nm$  regime the mode  $m = +18$  (which is cut-off in the presence of swirl) turns cut-off to cut-on in the fan region because of the swirl reduction. Considering the fundamental frequency ( $n = 1$ ) and the first harmonic( $n = 2$ ), Figure 17 actually evidences behaviour expected from basic mode/frequency scattering.

Following the scattering mode/frequency scattering rule, the mode  $m = +12$   
 515 is also expected at 3BPF ( $n = 3$ ) from the mode  $m = -12$  at 2BPF ( $n = 2$ ).  
 This is the case for the 41% $Nm$  regime but not for the 61% $Nm$  regime. This  
 difference between the two configurations is not well understood. It may be due  
 to a limited time resolution for the 61% $Nm$  regime that does not capture well  
 520 the higher frequencies.

Secondly, we identify a reflection mechanism of less magnitude for the modes  
 $m = -18$  and  $m = -12$ . Figure 20 illustrates this mechanism for both regimes.




Figure 19: Frequency and modal scattering of the mode  $m = -6(n = 1)$  into the mode  
 $m = +18(n = 2)$  for the 41% $Nm$  regime. — FAN-OGV-swirl — OGV-swirl




Figure 20: Reflection mechanism for modes  $m = -18$  at 41% $Nm$  regime (top) and  $m = -12$   
 at 61% $Nm$  regime. — FAN-OGV-swirl — OGV-swirl

## 5. Conclusion

In this paper, a numerical strategy to investigate the fan's screen effect  
525 on fan/OGV interaction tones was proposed. This strategy is based on the resolution of the two-dimensional linearized Euler equations in presence of axisymmetric swirling mean flow. To assess the source mechanism a scattering approach based on a fan wake model was employed.

Time-domain simulations were carried out on an unwrapped cylindrical layer  
530 using a high-order finite volume method based on Moving Least Squares approximations. The relative motion between the fan blades and the OGV blades was modelled using a high resolution sliding mesh technique.

The numerical results showed that the acoustic signature is clearly impacted by the presence of the fan in the computational domain. The modal analysis  
535 highlighted for the blade passing frequency (BPF) and the first harmonic the existence of key mechanisms : Tyler and Sofrin's modes experiences frequency and modal scattering where scattered modes are regenerated at other harmonics of the blade-passing frequency (BPF) and azimuthal orders shifted by a multiple of the fan blade number.

540 The obtained two-dimensional results are in accordance with analytical literature and they should not be fundamentally questioned when going to three-dimensional computations (only quantitatively modified). In spite of that, three-dimensional calculations are needed to reinforce the conclusions of this study. These calculations will also make it possible to analyse the behaviour of radial modes through the fan stage, which are a first concern in designing UHBR  
545 turbofans.

## Appendix A: Radiation from a flat plate subjected to a normal incidence gust

Let us consider the interaction between a  $x$ -direction flat plate airfoil of  
550 length  $l$  and a normal sinusoidal gust convected with the mean flow  $\bar{\mathbf{v}} = (\bar{u}, 0)$ .

The flow velocity in the  $x$ -direction is given by  $\bar{u} = M \times \bar{c}$  and the gust is defined as follows :

$$v(x) = \epsilon \cos(k_x x - \omega t) \quad (31)$$

where  $\epsilon$  is the gust amplitude,  $k_x$  is the wave number in the  $x$ -direction. The frequency of the gust is directly related to the wave-number in the  $x$ -direction through Taylor's hypothesis, as  $\omega = \bar{u} \times k_x$ .

Let us now write the LEE in conservative variables form in this specific case (uniform mean flow in the  $x$ -direction) :

$$\mathcal{S}(U) = \begin{cases} \frac{d\rho'}{dt} + \bar{\rho} \nabla \cdot \mathbf{v}' = 0 \\ \frac{d\bar{\rho}\mathbf{v}'}{dt} + \nabla(p') = 0 \\ \frac{dp'}{dt} + \gamma \bar{p} \nabla \cdot \mathbf{v}' = 0 \end{cases} \quad (32)$$

where  $\mathbf{U} = [\rho', \bar{\rho}\mathbf{v}', p']^T$  is the vector of conservative variables and  $\frac{d}{dt} = \frac{\partial}{\partial t} + \bar{u} \frac{\partial}{\partial x}$  is the convective derivative.

Starting from these equations, the field of fluctuating velocities is rewritten by separating the incident gust velocity, denoted by  $\mathbf{u}'_v = (0, v(x))$ , from the velocity field scattered by the plate, noted as  $\mathbf{u}'_a = (u', v')$ . Thus, we write :

$$\mathbf{v}' = \mathbf{u}'_v + \mathbf{u}'_a \quad (33)$$

Since the gust is solenoidal and convected by the mean flow as a "frozen" pattern, it is possible to write the two following equations :

$$\nabla \cdot \mathbf{u}'_v = 0 \quad (34)$$

$$\frac{d\mathbf{u}'_v}{dt} = 0 \quad (35)$$

565 By substituting the decomposition of the field of fluctuating velocities 33  
into the LEE system 32 and by using identities 34 and 35, we obtain :

$$\mathcal{S}(U_a) = \begin{cases} \frac{d\rho'}{dt} + \bar{\rho} \nabla \cdot \mathbf{u}'_a = 0 \\ \frac{d\bar{\rho}\mathbf{u}'_a}{dt} + \nabla(p') = 0 \\ \frac{dp'}{dt} + \gamma\bar{p} \nabla \cdot \mathbf{u}'_a = 0 \end{cases} \quad (36)$$

Identifying  $\mathcal{S}(U)$  and  $\mathcal{S}(U_a)$  means that the scattered field is only considered in the system of equations  $\mathcal{S}$  and its originates from the boundary condition on the flat plate airfoil [25]. It is in this sense that this method is called “scattering formulation”.

570 To compute the noise scattered on the flat plate from gust disturbances, one has to look at the expression of total velocity :

$$\mathbf{v} = \bar{\mathbf{v}} + \mathbf{u}_i + \mathbf{u}_s = (\bar{u} + u', v' + v(x)) \quad (37)$$

By exploiting the nullity of the normal component of the total velocity on the wall ( $\mathbf{v} \cdot \mathbf{n} = 0$ ), the boundary condition to apply follows as

$$v' = -v(x) \quad (38)$$

575 This validation case is carried out considering a length of the plate  $l$  equal to 1m. The Mach number of the mean flow is 0.5 while the relative amplitude of the gust  $\epsilon$  is set to 0.02. In order to address a non-compact plate case ( $\lambda_{\text{gust}} = 2\pi/k_x \simeq l$ ) the axial wave number  $k_x$  is set to  $6m^{-1}$ . To reach the steady-state more quickly the incident gust is introduced gradually using the factor  $(1 - e^{t/\tau})$ .

The computational domain is reduced to a half disk using the symmetry along the  $x$ -direction. It is divided in two parts : the physical zone  $\Omega_u = [0, \pi] \times [0, r_1]$  and the sponge zone  $\Omega_s = [0, \pi] \times [r_1, r_2]$  which is added to dissipate the energy of acoustic waves before waves fronts reach the boundary. The total 585 number of element is noted  $N$ .

We introduce the characteristic element size  $h$  to give a local measure of the mesh refinement. The characteristic element size on the plate is defined as  $h_p = N_p/l$  with  $N_p$  the number of element along the plate, whereas the characteristic element size on a half-circle at constant radius  $r_i$  is defined as  $h_{r_i} = N_{r_i}/\pi r_i$  with  $N_{r_i}$  the number of element along the half-circle. The simulation parameters and the computational domain are shown in figure 21.




Figure 21: Computational domain :  $r_1 = 5l$ ,  $r_2 = 7l$ . Numerical parameters :  $\Delta t = 2.0e - 5s$ ,  $CFL = 0.68$ ,  $N = 18700$ , Physical zone ( $\Omega_u$ ) :  $h_p \simeq 0.01$ ,  $h_{r_1} \simeq 0.13$ ,  $\chi = 1.05$ , Sponge zone ( $\Omega_s$ ) :  $h_{r_1} \simeq 0.13$ ,  $h_{r_2} \simeq 0.324$ ,  $\chi = 1.1$ . gust's parameters :  $\epsilon = 0.02$ ,  $M = 0.5$ ,  $k_x = 6m^{-1}$ ,  $l = 1m$ .

The numerical implementation of the scattering formulation is validated in comparison with Amiet's model which is based on the same assumptions. The directivity pattern of this interaction is computed by using the RMS pressure along the radius  $r_{RMS} = 4l = 4m$ . As shown in figure 22, it is in good agreement with Amiet's directivity. In particular, the side lobe which is caused by the non compactness of the plate, is captured by the numerical scheme.




Figure 22: Directivity diagram : RMS pressure over 50 periods compared to Amiet's solution (from [16]).

## Appendix B: Moving Least Squares approximations

The Moving Least Squares approximation is a very usual technique in the  
600 meshless community. It is very well suited for the approximation of scattered  
data. For the sake of brevity, this numerical scheme will be summarized here,  
and we refer the reader to [40, 41, 42, 30] for further details. The main fea-  
ture is that the MLS functions are used to construct a high order continuous  
representation of the solution  $\mathbf{U}(\mathbf{x})$  and then its space derivatives. The general  
605 representation of  $\mathbf{U}(\mathbf{x})$  is a continuous function  $\widehat{\mathbf{U}}(\mathbf{x})$  of the form

$$\widehat{\mathbf{U}}(\mathbf{x}) = \sum_{J \in \mathcal{S}_{\mathbf{x}}} N_J(\mathbf{x}) \mathbf{U}_J \quad (39)$$

where  $\mathcal{S}_{\mathbf{x}}$  is the neighborhood or *stencil* of the approximation point,  $J$  is the  
identifier of the cells inside the stencil,  $\mathbf{U}_J$  is the centroid variable of the J-cell  
and  $N_J(\mathbf{x})$  is the MLS-shape function which weighs the J-cell.

To compute the MLS shape functions we define an  $n_{\min}$ -dimensional ba-  
610 sis, which in this case is defined as  $\mathbf{p}^T(\mathbf{x}) = (1, x, y, z, x^2, y^2, z^2, xy, \dots) \in R^{n_{\min}}$ .  
Shape functions are computed on the J-cell by using a weighted least-squares  
fitting procedure centered at the point  $\mathbf{x}$ . In this work, the stencil of the  
J-cell is comprised by  $n_t$  neighbors, including the J-cell itself. Thus,  $\forall J$ ,  
615  $\text{card}(\mathcal{S}_{\mathbf{x}}) = n_t$ . The minimum number of points in the stencil corresponds to  
the dimension of the polynomial basis used in the interpolation. It is given  
by  $n_{\min} = (p_{\text{MLS}} + 1)(p_{\text{MLS}} + 2)/2$  (in 2D) where  $p_{\text{MLS}}$  is the polynomial order  
of the approximation. Here we use a cubic reconstruction polynomial for the  
computations. If  $n_t = n_{\min}$ , the FV-MLS scheme becomes unstable. To solve  
620 this problem, we introduce an additional number of points  $n_{\text{add}} = 10$  such as  
 $n_t = n_{\min} + n_{\text{add}}$  which depends on both the reconstruction order and skewness  
of the grid. Details can be found in [40, 41, 42, 30].

Thus, the  $n_t$  MLS-shape funtions associated with the J-cell, in equation 39  
are defined as [40]

$$\mathbf{N}^T(\mathbf{x}) = \mathbf{p}^T(\mathbf{x}) \mathbf{C}^{-1}(\mathbf{x}) \mathbf{P}(\mathbf{x}) \mathbf{W}(\mathbf{x}) \quad (40)$$

where  $\mathbf{P} = [\mathbf{p}^T(\mathbf{x}_j)]_j$ , is a  $n_{\min} \times n_t$  matrix where the basis functions are evaluated at each point of the stencil, and  $\mathbf{C}(\mathbf{x})$  is the  $n_{\min} \times n_{\min}$  moment matrix given by

$$\mathbf{C}(\mathbf{x}) = \mathbf{P}(\mathbf{x})\mathbf{W}(\mathbf{x})\mathbf{P}^T(\mathbf{x}). \quad (41)$$

The  $n_t$ -diagonal matrix  $\mathbf{W}(\mathbf{x})$  is built by evaluation of a *kernel* function  $(W)$  at the point  $\mathbf{x}$ . This function weight the values of each centroid inside the stencil. In this work an exponential kernel function [41] is used. It reads as

$$W(x, x^2, \kappa_x) = \frac{e^{-(\frac{s}{c})^2} - e^{-(\frac{d_m}{c})^2}}{1 - e^{-(\frac{d_m}{c})^2}} \quad (42)$$

with  $s = |x_j - x^2|$ ,  $d_m = \max(|x_j - x^2|)$ , with  $j = 1, \dots, n_{x^*}$ ,  $c = \frac{d_m}{2\kappa}$ ,  $x$  is the position of every cell centroid of the stencil and  $\kappa$  is a shape parameter. The dispersion and dissipation properties of the FV-MLS method are strongly related to the choice of the shape parameter  $\kappa$  [41] of the exponential kernel. A value of  $\kappa = 5$  is used here.

The derivatives of the function can also be computed by using the derivatives of the MLS-shape functions

$$\nabla \widehat{\mathbf{U}}(\mathbf{x}) = \sum_{J \in \mathcal{S}_{\mathbf{x}}} \nabla N_J(\mathbf{x}) \mathbf{U}_J \quad (43)$$

### Acknowledgements

Xesús Nogueira and Luis Ramírez acknowledge the support given by FEDER funds of the European Union, Grants #DPI2015-68431-R of the *Ministerio de Economía y Competitividad* and #RTI2018-093366-B-I00 of the *Ministerio de Ciencia, Innovación y Universidades* of the Spanish Government, and by the *Consellería de Cultura, Educación e Ordenación Universitaria* of the Xunta de Galicia (program *Axudas para potenciación de grupos de investigación do Sistema Universitario de Galicia 2018*, grant # ED431C 2018/41) . .

## References

- [1] E. Envia, A. G. Wilson, D. L. Huff, Fan noise: a challenge to caa, *International Journal of Computational Fluid Dynamics* 18 (6) (2004) 471–480.
- 645 [2] D. B. Hanson, Acoustic reflection and transmission of rotors and stators including mode and frequency scattering, in: 3rd AIAA/CEAS Aeroacoustics Conference, 1997, p. 1610.
- 650 [3] P. D. Silkowski, K. C. Hall, A coupled mode analysis of unsteady multi-stage flows in turbomachinery, in: ASME 1997 International Gas Turbine and Aeroengine Congress and Exhibition, American Society of Mechanical Engineers, 1997, pp. V004T14A033–V004T14A033.
- [4] D. B. Hanson, Broadband noise of fans-with unsteady coupling theory to account for rotor and stator reflection/transmission effects.
- 655 [5] H. Posson, S. Moreau, Effect of rotor shielding on fan-outlet guide vanes broadband noise prediction, *AIAA journal* 51 (7) (2013) 1576–1592.
- [6] S. Bouley, B. François, M. Roger, H. Posson, S. Moreau, On a two-dimensional mode-matching technique for sound generation and transmission in axial-flow outlet guide vanes, *Journal of Sound and Vibration* 403 (2017) 190–213.
- 660 [7] J. De Laborderie, S. Moreau, Prediction of tonal ducted fan noise, *Journal of Sound and Vibration* 372 (2016) 105–132.
- [8] N. C. Ovenden, S. W. Rienstra, Mode-matching strategies in slowly varying engine ducts, *AIAA journal* 42 (9) (2004) 1832–1840.
- 665 [9] C. Weckmüller, S. Guérin, G. Ashcroft, Cfd/caa coupling applied to dlr uhbr-fan: Comparison to experimental data, in: 15th AIAA/CEAS Aeroacoustics Conference (30th AIAA Aeroacoustics Conference), 2009, p. 3342.

- [10] C. Polacsek, S. Burguburu, S. Redonnet, M. Terracol, Numerical simulations of fan interaction noise using a hybrid approach, *AIAA journal* 44 (6) (2006) 1188–1196.
- 670 [11] X. Zhang, X. Chen, C. Morfey, P. Nelson, Computation of spinning modal radiation from an unflanged duct, *AIAA journal* 42 (9) (2004) 1795–1801.
- [12] H. Posson, N. Peake, The acoustic analogy in an annular duct with swirling mean flow, *Journal of Fluid Mechanics* 726 (2013) 439–475.
- 675 [13] T. Suzuki, P. R. Spalart, M. Shur, M. Strelets, A. Travin, Unsteady simulations of a fan/outlet-guide-vane system. part 2: Tone noise computation, in: 23rd AIAA/CEAS Aeroacoustics Conference, 2017, p. 3876.
- [14] H. Atassi, A. Kozlov, A. Ali, D. Topol, Coupled fan–stator aerodynamic and acoustic response to inflow distortion, *Journal of Turbomachinery* 141 (10).
- 680 [15] M. Nallasamy, R. Hixon, S. Sawyer, Computed linear/nonlinear acoustic response of a cascade for single/multi frequency excitation, in: 10th AIAA/CEAS Aeroacoustics Conference, 2004, p. 2998.
- 685 [16] V. Clair, Calcul numérique de la réponse acoustique d'un aubage soumis à un sillage turbulent (numerical computation of the acoustic response of a vane under the action of a turbulent wake), Ph.D. thesis, Université Claude Bernard-Lyon I (2013).
- [17] A. Sescu, R. Hixon, S. Sawyer, Validation of a caa code using a benchmark wake-stator interaction problem, *AIAA Paper* 3340 (2009) 2009.
- 690 [18] R. Hixon, A. Sescu, V. Allampalli, Reprint of: Towards the prediction of noise from realistic rotor wake/stator interaction using caa, *Procedia IUTAM* 1 (2010) 203–213.
- [19] E. Envia, Benchmark solution for the category 3, problem 2: Cascade-gust interaction, Fourth Computational Aeroacoustics (CAA) Workshop on

- Benchmark Problems, p. 59-65; NASA/CP-2004-212954.
- 695 URL <https://ntrs.nasa.gov/archive/nasa/casi.ntrs.nasa.gov/20040182277.pdf>
- [20] T. Hainaut, G. Gabard, V. Clair, A caa study of turbulence distortion in broadband fan interaction noise, in: 22nd AIAA/CEAS Aeroacoustics Conference, 2016, p. 2839.
- 700 [21] H.-n. Chen, A. Sharma, C. Shieh, S. Richards, Linearized navier-stokes analysis for rotor-stator interaction tone noise prediction, in: 16th AIAA/CEAS Aeroacoustics Conference, 2010, p. 3744.
- [22] H. Atassi, A. Ali, O. Atassi, I. Vinogradov, Scattering of incident disturbances by an annular cascade in a swirling flow, *Journal of fluid mechanics* 499 (2004) 111–138.
- 705 [23] B. Bouley, B. François, M. Roger, Modèle analytique du bruit d’interaction rotor/stator dans les turbomachines axiales par la méthode de raccordement modal (analytical model of the rotor/stator interaction noise in axial turbomachines by using the modal connection method), in: CFA/VISHNO 2016, 2016, p. 673.
- [24] B. Reynolds, B. Lakshminarayana, A. Ravindranath, Characteristics of the near wake of a compressor of a fan rotor blade, *AIAA Journal* 17 (9) (1979) 959–967.
- 715 [25] J. Scott, S. Hariharan, R. Mankbadi, Evaluation of numerical schemes for the analysis of sound generation by blade-gust interaction, in: NASA CONFERENCE PUBLICATION, NASA, 1995, pp. 303–303.
- [26] S. K. Godunov, A difference method for numerical calculation of discontinuous solutions of the equations of hydrodynamics, *Matematicheskii Sbornik* 89 (3) (1959) 271–306.

- 720 [27] K. Šalkauskas, Moving least squares interpolation with thin-plate splines  
and radial basis functions, *Computers & Mathematics with Applications*  
24 (12) (1992) 177–185.
- [28] E. F. Toro, *Riemann solvers and numerical methods for fluid dynamics: a practical introduction*, Springer Science & Business Media, 2013.
- 725 [29] C. Foulquié, S. Khelladi, M. Deligant, J. Mardjono, M. Henner, High-order aeroacoustics propagation solver with sliding-mesh capabilities for subsonic turbomachinery, in: *22nd AIAA/CEAS Aeroacoustics Conference*, 2016, p. 2723.
- [30] S. Khelladi, X. Nogueira, F. Bakir, I. Colominas, Toward a higher order  
730 unsteady finite volume solver based on reproducing kernel methods, *Computer Methods in Applied Mechanics and Engineering* 200 (29-32) (2011)  
2348–2362.
- [31] G. W. Stewart, *Matrix Algorithms: Basic Decompositions*, SIAM, Society for industrial and applied mathematics, p. 55, ISBN 0-89871-414-1, 1998.
- 735 [32] C. A. Kennedy, M. H. Carpenter, R. M. Lewis, Low-storage, explicit runge-kutta schemes for the compressible navier–stokes equations, *Applied numerical mathematics* 35 (3) (2000) 177–219.
- [33] L. Ramírez, C. Foulquié, X. Nogueira, S. Khelladi, J.-C. Chassaing,  
I. Colominas, New high-resolution-preserving sliding mesh techniques for  
740 higher-order finite volume schemes, *Computers & Fluids* 118 (2015) 114–130.
- [34] S. Kamil, K. Datta, S. Williams, L. Oliker, J. Shalf, K. Yelick, Implicit and explicit optimizations for stencil computations, in: *Proceedings of the 2006 workshop on Memory system performance and correctness*, 2006, pp. 51–60.
- 745 [35] C. Bogey, C. Bailly, D. Juvé, Computation of flow noise using source terms in linearized euler’s equations, *AIAA journal* 40 (2) (2002) 235–243.

- [36] J. M. Tyler, T. G. Sofrin, Axial flow compressor noise studies, Tech. rep., SAE Technical Paper (1962).
- 750 [37] J. Mathews, J. Chen, P. Joseph, Modal cut-on ratio in ducts with realistic flow profiles and its application to acoustic mode detection, *Journal of Sound and Vibration* 434 (2018) 404–421.
- 755 [38] S. Bouley, Modélisations analytiques du bruit tonal d'interaction rotor/stator par la technique de raccordement modal, Ph.D. thesis, Lyon (2017).
- [39] D. B. Hanson, Broadband noise of fans – with unsteady coupling theory to account for rotor and stator reflection/transmission effects, in: NASA CR-2001-211136, 2001.
- 760 [40] X. Nogueira, L. Cueto-Felgueroso, I. Colominas, H. Gómez, F. Navarrina, M. Casteleiro, On the accuracy of finite volume and discontinuous galerkin discretizations for compressible flow on unstructured grids, *International Journal for Numerical Methods in Engineering* 78 (13) (2009) 1553–1584.
- 765 [41] X. Nogueira, I. Colominas, L. Cueto-Felgueroso, S. Khelladi, On the simulation of wave propagation with a higher-order finite volume scheme based on reproducing kernel methods, *Computer Methods in Applied Mechanics and Engineering* 199 (23-24) (2010) 1471–1490.
- 770 [42] X. Nogueira, I. Colominas, L. Cueto-Felgueroso, S. Khelladi, F. Navarrina, M. Casteleiro, Resolution of computational aeroacoustics problems on unstructured grids with a higher-order finite volume scheme, *Journal of Computational and Applied Mathematics* 234 (7) (2010) 2089–2097.